



ZOOMLION

Серия РМ

Технические характеристики

По вопросам продаж и поддержки обращайтесь:

Архангельск (8182)63-90-72	Калининград (4012)72-03-81	Нижний Новгород (831)429-08-12	Смоленск (4812)29-41-54
Астана +7(7172)727-132	Калуга (4842)92-23-67	Новокузнецк (3843)20-46-81	Сочи (862)225-72-31
Белгород (4722)40-23-64	Кемерово (3842)65-04-62	Новосибирск (383)227-86-73	Ставрополь (8652)20-65-13
Брянск (4832)59-03-52	Киров (8332)68-02-04	Орел (4862)44-53-42	Тверь (4822)63-31-35
Владивосток (423)249-28-31	Краснодар (861)203-40-90	Оренбург (3532)37-68-04	Томск (3822)98-41-53
Волгоград (844)278-03-48	Красноярск (391)204-63-61	Пенза (8412)22-31-16	Тула (4872)74-02-29
Вологда (8172)26-41-59	Курск (4712)77-13-04	Пермь (342)205-81-47	Тюмень (3452)66-21-18
Воронеж (473)204-51-73	Липецк (4742)52-20-81	Ростов-на-Дону (863)308-18-15	Ульяновск (8422)24-23-59
Екатеринбург (343)384-55-89	Магнитогорск (3519)55-03-13	Рязань (4912)46-61-64	Уфа (347)229-48-12
Иваново (4932)77-34-06	Москва (495)268-04-70	Самара (846)206-03-16	Челябинск (351)202-03-61
Ижевск (3412)26-03-58	Мурманск (8152)59-64-93	Санкт-Петербург (812)309-46-40	Череповец (8202)49-02-64
Казань (843)206-01-48	Набережные Челны (8552)20-53-41	Саратов (845)249-38-78	Ярославль (4852)69-52-93

сайт: www.zoomlion.nt-rt.ru || эл. почта: znm@nt-rt.ru

ZOOMLION ZLJ5070GXFP30 FIRE VEHICLE

Technical Specifications



Brief Code	PM30
Model Name	ZLJ5070GXFP30
Main Notes	Water tank: 2000 L Foam tank: 550 L Pump flow: 1800 lpm (480 USgpm)
FEATURES	All-aluminum body and stainless steel tank. Light weight, and will never rust. Stainless steel pipelines Centralized control panel that makes operation and use extremely easy. Variety hose connectors. With manhole at the top of the water pump room. With normal foam extinguishing system.
Overall Measurement (L*W*H)	6850*2040*2620 mm
Chassis Brand	ISUZU QL1070A1KWY
Driving form	4*2
Wheel Base	3815 mm
Curb Mass	3855 kg
GVW	6780 kg
Water Tank Capacity	2000 L

Foam Tank Capacity	550 L
Engine Power	88 kW (120 HP)
Power Density	12.8 kW/t
Max Vehicle Speed	105 km/h
Fire Pump Model	CB10/30-XZ
Monitor Model	PL24
Water Pump Flow	1800 lpm (480 USgpm)
Water Pump Pressure	1 MPa
Monitor Flow Rate	1440 lpm (390 USgpm)
Monitor Range	≥ 40 m
Water Pumper Inlet Diameter	1*100 mm
Water Pumper Outlet Diameter	2*80 mm(normal pressure)
Water Tank Inlet Diameter	2*65 mm (1 for each side)
Proportioning Mixer	PH32
Driver's Cab	5 persons

ZOOMLION ZLJ5200GXFPM80 FIRE VEHICLE

Technical Specifications



Brief Code	PM80
Model Name	ZLJ5200GXFPM80
Main Notes	Water tank: 5600 L Foam tank: 2300 L Pump flow: 3600 lpm (960 USgpm)
FEATURES	All-aluminum body and stainless steel tank. Light weight, and will never rust. Stainless steel pipelines Centralized control panel that makes operation and use extremely easy. Variety hose connectors. With manhole at the top of the water pump room. With normal foam extinguishing system. High flow rate.
Overall Measurement (L*W*H)	8695*2500*380 mm
Chassis Brand	SINOTRUK ZZ5207M4617D5
Driving form	4*2
Wheel Base	4600 mm
Curb Mass	11950 kg
GVW	20300 kg
Water Tank Capacity	5600 L

Foam Tank Capacity	2300 L
Engine Power	228 kW (310 HP)
Power Density	11.2 kW/t
Max Vehicle Speed	100 km/h
Min Turning Diameter	18 m
Fire Pump Model	CB20.10/30.60-XZ
Monitor Model	PS50
Water Pump Flow	3600/1800 lpm (960/480 USgpm)
Water Pump Pressure	1.0/2.0 MPa
Monitor Flow Rate	2880 lpm (770 USgpm)
Monitor Range	≥55 m
Water Pumper Inlet Diameter	1*150 mm
Water Pumper Outlet Diameter	4*80 mm(normal pressure) & 2*65 mm(medium pressure)
Water Tank Inlet Diameter	2*80 mm(1 for each side)
Proportioning Mixer	PH48
Driver's Cab	6 persons

ZOOMLION ZLJ5280GXFPM120 FIRE VEHICLE

Technical Specifications



Brief Code	PM120
Model Name	ZLJ5280GXFPM120
Main Notes	Water tank: 10000 L Foam tank: 2300 L Pump flow: 3600 lpm (960 USgpm)
FEATURES	All-aluminum body and stainless steel tank. Light weight, and will never rust. Stainless steel pipelines Centralized control panel that makes operation and use extremely easy. Variety hose connectors. With manhole at the top of the water pump room. With normal foam extinguishing system. High flow rate. Remote control monitor.
Overall Measurement (L*W*H)	10050*2500*3400 mm
Chassis Brand	SINOTRUK ZZ5347V4647D5

Driving form	6*4
Wheel Base	4600+1350 mm
Curb Mass	14900 kg
GVW	27650 kg
Outrigger Transversal Span	
Water Tank Capacity	10000 L
Foam Tank Capacity	2300 L
Engine Power	276 kW (375 HP)
Power Density	9 kW/t
Max Vehicle Speed	90 km/h
Min Turning Diameter	20 m
Fire Pump Model	CB20.10/30.60-XZ (US made HALE is optional)
Monitor Model	PL48 (US made AKRON is optional)
Water Pump Flow	3600/1800 lpm (960/480 USgpm)
Water Pump Pressure	1.0/2.0 MPa
Monitor Flow Rate	2880 lpm (770 USgpm)
Monitor Range	≥60 m
Water Pumper Inlet Diameter	1*150 mm
Water Pumper Outlet Diameter	4*80 mm(normal pressure) & 2*65 mm(medium pressure)
Water Tank Inlet Diameter	4*80 mm(2 for each side)
Proportioning Mixer	PH64
Driver's Cab	6 persons

ZOOMLION ZLJ5330GXFPM180 FIRE VEHICLE

Technical Specifications



Brief Code	PM180
Model Name	ZLJ5330GXFPM180
Main Notes	Water tank: 15250 L Foam tank: 2350 L Pump flow: 3600 lpm (960 USgpm)
FEATURES	All-aluminum body and stainless steel tank. Light weight, and will never rust. Stainless steel pipelines Centralized control panel that makes operation and use extremely easy. Variety hose connectors. With manhole at the top of the water pump room. With normal foam extinguishing system. High flow rate.
Overall Measurement (L*W*H)	10430*2500*3680 mm
Chassis Brand	SINOTRUK ZZ5347V4647D1

Driving form	6*4
Wheel Base	4600+1350 mm
Curb Mass	15440 kg
GVW	33490 kg
Water Tank Capacity	15250 L
Foam Tank Capacity	2350 L
Engine Power	276 kW (375 HP)
Power Density	8.2 kW/t
Max Vehicle Speed	80 km/h
Min Turning Diameter	22 m
Fire Pump Model	CB20. 10/30. 60-TB
Monitor Model	PL48
Water Pump Flow	3600/1800 lpm (960/480 USgpm)
Water Pump Pressure	1.0/2.0 MPa
Monitor Flow Rate	2880 lpm (770 USgpm) foam monitor
Monitor Range	≥60 m
Water Pumper Inlet Diameter	1*135 mm
Water Pumper Outlet Diameter	4*80 mm(normal pressure) & 2*65 mm(medium pressure)
Water Tank Inlet Diameter	4*80 (2 for each side)
Proportioning Mixer	Integrated
Driver's Cab	6 persons

ZOOMLION ZLJ5430GXFPM250 FIRE VEHICLE

Technical Specifications



Brief Code	PM250
Model Name	ZLJ5430GXFPM250
Main Notes	Water tank: 20000 L Foam tank: 4550 L Pump flow: 4800 lpm (1270 USgpm)
FEATURES	All-aluminum body and stainless steel tank. Light weight, and will never rust. Stainless steel pipelines Centralized control panel that makes operation and use extremely easy. Variety hose connectors. With manhole at the top of the water pump room. With normal foam extinguishing system. High flow rate. Remote control monitor.
Overall Measurement (L*W*H)	12050*2500*3580 mm
Chassis Brand	SINOTRUK ZZ5437V4667D1
Driving form	8*4

Wheel Base	1800+4600+13500 mm
Curb Mass	17900 kg
GVW	42600 kg
Outrigger Transversal Span	
Water Tank Capacity	20000 L
Foam Tank Capacity	4550 L
Engine Power	309 kW (420 HP)
Power Density	6.96 kW/t
Max Vehicle Speed	80 km/h
Min Turning Diameter	24 m
Fire Pump Model	CB10/100-TB (US made HALE is optional)
Monitor Model	PL64 (US made AKRON is optional)
Water Pump Flow	4800 lpm (1270 USgpm)
Water Pump Pressure	1 MPa
Monitor Flow Rate	3840 lpm (1020 USgpm) foam monitor
Monitor Range	≥65 (foam monitor)
Water Pumper Inlet Diameter	1*150 mm
Water Pumper Outlet Diameter	4*80 mm(2 for each side)
Water outlet at cage	
Water Tank Inlet Diameter	4*80 mm(2 for each side)
Foam suction inlet	
Proportioning Mixer	Integrated
Driver's Cab	2 persons

The logo for ZOOMLION, featuring the word "ZOOMLION" in a bold, dark blue, sans-serif font. The text is centered within a light green rectangular background that has a diagonal cut on its right side.

По вопросам продаж и поддержки обращайтесь:

Архангельск (8182)63-90-72	Калининград (4012)72-03-81	Нижний Новгород (831)429-08-12	Смоленск (4812)29-41-54
Астана +7(7172)727-132	Калуга (4842)92-23-67	Новокузнецк (3843)20-46-81	Сочи (862)225-72-31
Белгород (4722)40-23-64	Кемерово (3842)65-04-62	Новосибирск (383)227-86-73	Ставрополь (8652)20-65-13
Брянск (4832)59-03-52	Киров (8332)68-02-04	Орел (4862)44-53-42	Тверь (4822)63-31-35
Владивосток (423)249-28-31	Краснодар (861)203-40-90	Оренбург (3532)37-68-04	Томск (3822)98-41-53
Волгоград (844)278-03-48	Красноярск (391)204-63-61	Пенза (8412)22-31-16	Тула (4872)74-02-29
Вологда (8172)26-41-59	Курск (4712)77-13-04	Пермь (342)205-81-47	Тюмень (3452)66-21-18
Воронеж (473)204-51-73	Липецк (4742)52-20-81	Ростов-на-Дону (863)308-18-15	Ульяновск (8422)24-23-59
Екатеринбург (343)384-55-89	Магнитогорск (3519)55-03-13	Рязань (4912)46-61-64	Уфа (347)229-48-12
Иваново (4932)77-34-06	Москва (495)268-04-70	Самара (846)206-03-16	Челябинск (351)202-03-61
Ижевск (3412)26-03-58	Мурманск (8152)59-64-93	Санкт-Петербург (812)309-46-40	Череповец (8202)49-02-64
Казань (843)206-01-48	Набережные Челны (8552)20-53-41	Саратов (845)249-38-78	Ярославль (4852)69-52-93

сайт: www.zoomlion.nt-rt.ru || эл. почта: znm@nt-rt.ru