



ZOOMLION

Серия УТ

Технические характеристики

По вопросам продаж и поддержки обращайтесь:

Архангельск (8182)63-90-72	Калининград (4012)72-03-81	Нижний Новгород (831)429-08-12	Смоленск (4812)29-41-54
Астана +7(7172)727-132	Калуга (4842)92-23-67	Новокузнецк (3843)20-46-81	Сочи (862)225-72-31
Белгород (4722)40-23-64	Кемерово (3842)65-04-62	Новосибирск (383)227-86-73	Ставрополь (8652)20-65-13
Брянск (4832)59-03-52	Киров (8332)68-02-04	Орел (4862)44-53-42	Тверь (4822)63-31-35
Владивосток (423)249-28-31	Краснодар (861)203-40-90	Оренбург (3532)37-68-04	Томск (3822)98-41-53
Волгоград (844)278-03-48	Красноярск (391)204-63-61	Пенза (8412)22-31-16	Тула (4872)74-02-29
Вологда (8172)26-41-59	Курск (4712)77-13-04	Пермь (342)205-81-47	Тюмень (3452)66-21-18
Воронеж (473)204-51-73	Липецк (4742)52-20-81	Ростов-на-Дону (863)308-18-15	Ульяновск (8422)24-23-59
Екатеринбург (343)384-55-89	Магнитогорск (3519)55-03-13	Рязань (4912)46-61-64	Уфа (347)229-48-12
Иваново (4932)77-34-06	Москва (495)268-04-70	Самара (846)206-03-16	Челябинск (351)202-03-61
Ижевск (3412)26-03-58	Мурманск (8152)59-64-93	Санкт-Петербург (812)309-46-40	Череповец (8202)49-02-64
Казань (843)206-01-48	Набережные Челны (8552)20-53-41	Саратов (845)249-38-78	Ярославль (4852)69-52-93

сайт: www.zoomlion.nt-rt.ru || эл. почта: znm@nt-rt.ru

ZOOMLION ZLJ5151JXFYT25 Aerial Ladder and Platform

Technical Specifications



Brief Code	YT25A
Model Name	ZLJ5151JXFYT25
Main Notes	Ladder Height: 25 m Pump flow: 2400 lpm (640 USgpm)
FEATURES	Ladder height 25 meters, excellent for aerial rescue and extinguishing. Safety Protection including inter lock, fault operation alarm and automatic emergency stop system . Boom movement buffering system. Boom and cage automatic anti-collision system. Soft leg prevention. Automatic engine speed control when operation. One key outrigger stretching system.

	Smart combined movement of swivel and stretch. All-aluminum body and stainless steel tank. Light weight, and will never rust. Stainless steel pipelines Centralized control panel that makes operation and use extremely easy. Variety hose connectors. With normal foam extinguishing system. High flow rate. Remote control monitor.
Overall Measurement (L*W*H)	11080*2500*3700 mm
Chassis Brand	DONGFENG DFL5160XXYBX1A (BENZ optional)
Driving form	4*2
Wheel Base	5600 mm
Curb Mass	15090 kg
GVW	15240 kg
Outrigger Transversal Span	4500 mm
Engine Power	155 kW (211 HP) CUMMINS ISDe210 40, 6 cylinder
Power Density	9 kW/t
Max Vehicle Speed	≥90 km/h
Min Turning Diameter	18 m
Fire Pump Model	PSKD40W
Monitor Flow Rate	2400 lpm (640 USgpm)
Monitor Range	>60 m(water) >45 m(foam)
Water Pumper Outlet Diameter	1*KY65
Monitor Swivel Angle	-45 to 45 °
Monitor Pitch Angle	-45 to 90 °
Driver's Cab	3 persons
Max Working Height	25 (from ground to the cage bottom) m
Max Working Range	18 m
Cage rated capacity	300 kg
The action time of the boom	<90 s
Outrigger Stretching Time	<40 s
Max allowed wind speed	12.5 m/s

ZOOMLION ZLJ5320JXFYT32 Aerial Ladder and Platform

Technical Specifications



Brief Code	YT32F
Model Name	ZLJ5320JXFYT32
Main Notes	Ladder Height: 32 m Water tank: 3000 L CAFS Foam tank: 2000 L CAFS Pump flow: 3600 lpm (960 USgpm) With Class A Foam
FEATURES	Ladder height 32 meters, excellent for aerial rescue and extinguishing. Safety Protection including inter lock, fault operation alarm and automatic emergency stop system . Boom movement buffering system. Boom and cage automatic anti-collision system. Soft leg prevention. Automatic engine speed control when operation. One key outrigger stretching system. Smart combined movement of swivel and stretch.

	All-aluminum body and stainless steel tank. Light weight, and will never rust. Stainless steel pipelines Centralized control panel that makes operation and use extremely easy. Variety hose connectors. With manhole at the top of the water pump room. With CAFS Class A foam extinguishing system. High flow rate. Remote control monitor.
Overall Measurement (L*W*H)	12850*2500*3960 mm
Chassis Brand	BENZ Actros 3341
Driving form	6*4
Wheel Base	4500+13500 mm
Curb Mass	29350 kg
GVW	31600 kg
Outrigger Transversal Span	5490 mm
Water Tank Capacity	3000 L
Foam Tank Capacity	2000 L
Engine Power	300 kW (408 HP)
Power Density	8.5 kW/t
Max Vehicle Speed	≥90 km/h
Min Turning Diameter	21.8 m
Class A Foam System	
Fire Pump Model	DARLEY PSP1500 (integrated)
Monitor Model	AKRON 3578 (US made)
Water Pump Flow	5400 lpm (1430 USgpm)
Water Pump Pressure	
Monitor Flow Rate	4800 lpm (1270 USgpm)
Monitor Range	>80 m(water) >70 m(foam)
Water Pumper Inlet Diameter	2*150 mm (1 for each side)
Water Pumper Outlet Diameter	4*80 mm(2 for each side)
Water outlet at cage	1*65 mm
Water Tank Inlet Diameter	4*80 mm(2 for each side)
Foam suction inlet	1*40 mm
Proportioning Mixer	
Foam proportion	Adjustable Round Pump Integrated
Monitor Swivel Angle	-45 to 45 °
Monitor Pitch Angle	-45 to 90 °
Driver's Cab	2 persons

Max Working Height	32 (from ground to the cage bottom) m
Max Working Range	19 m
Cage rated capacity	450 kg
The action time of the boom	<100 s
Outrigger Stretching Time	<40 s
Max allowed wind speed	12.5 m/s

ZOOMLION ZLJ5300JXFYT53 Aerial Ladder and Platform

Technical Specifications



Brief Code	YT53C
Model Name	ZLJ5300JXFYT53
Main Notes	Ladder Height: 53 m

FEATURES

Ladder height 53 meters, excellent for aerial rescue and extinguishing.

Safety Protection including inter lock, fault operation alarm and automatic emergency stop system .

Boom movement buffering system.

Boom and cage automatic anti-collision system.

Soft leg prevention.

Automatic engine speed control when operation.

One key outrigger stretching system.

Smart combined movement of swivel and stretch.

All-aluminum body and stainless steel tank.

Light weight, and will never rust.

Stainless steel pipelines

Centralized control panel that makes operation and use extremely easy.

Variety hose connectors.

High flow rate.

Remote control monitor.

Overall Measurement (L*W*H)	12940*2500*3960 mm
Chassis Brand	BENZ Actros 3344
Driving form	6*4
Wheel Base	4800+1350 mm
Curb Mass	29850 kg
GVW	30000 kg
Outrigger Transversal Span	5300 mm
Engine Power	320 kW (435 HP)
Power Density	9.6 kW/t
Max Vehicle Speed	≥90 km/h
Min Turning Diameter	21.5 m
Monitor Model	AKRON 3463 (US made)
Water Pump Flow	2100 lpm (560 USgpm)
Monitor Range	>60 m(water) >55 m(foam)
Water Pumper Outlet Diameter	4*80 mm(2 for each side)
Monitor Swivel Angle	-45 to 45 °
Monitor Pitch Angle	-45 to 90 °
Driver's Cab	2 persons
Max Working Height	53 (from ground to the cage bottom) m
Max Working Range	18 m
Platform cage rated capacity	225 kg
Sliding bucket capacity	150 kg
The action time of the boom	<150 s

Outrigger Stretching Time	<40 s
Max allowed wind speed	12.5 m/s

The logo for ZOOMLION, featuring the word "ZOOMLION" in a bold, dark blue, sans-serif font. The text is centered within a light green rectangular background that has a diagonal cut on its right side.

По вопросам продаж и поддержки обращайтесь:

Архангельск (8182)63-90-72	Калининград (4012)72-03-81	Нижний Новгород (831)429-08-12	Смоленск (4812)29-41-54
Астана +7(7172)727-132	Калуга (4842)92-23-67	Новокузнецк (3843)20-46-81	Сочи (862)225-72-31
Белгород (4722)40-23-64	Кемерово (3842)65-04-62	Новосибирск (383)227-86-73	Ставрополь (8652)20-65-13
Брянск (4832)59-03-52	Киров (8332)68-02-04	Орел (4862)44-53-42	Тверь (4822)63-31-35
Владивосток (423)249-28-31	Краснодар (861)203-40-90	Оренбург (3532)37-68-04	Томск (3822)98-41-53
Волгоград (844)278-03-48	Красноярск (391)204-63-61	Пенза (8412)22-31-16	Тула (4872)74-02-29
Вологда (8172)26-41-59	Курск (4712)77-13-04	Пермь (342)205-81-47	Тюмень (3452)66-21-18
Воронеж (473)204-51-73	Липецк (4742)52-20-81	Ростов-на-Дону (863)308-18-15	Ульяновск (8422)24-23-59
Екатеринбург (343)384-55-89	Магнитогорск (3519)55-03-13	Рязань (4912)46-61-64	Уфа (347)229-48-12
Иваново (4932)77-34-06	Москва (495)268-04-70	Самара (846)206-03-16	Челябинск (351)202-03-61
Ижевск (3412)26-03-58	Мурманск (8152)59-64-93	Санкт-Петербург (812)309-46-40	Череповец (8202)49-02-64
Казань (843)206-01-48	Набережные Челны (8552)20-53-41	Саратов (845)249-38-78	Ярославль (4852)69-52-93

сайт: www.zoomlion.nt-rt.ru || эл. почта: znm@nt-rt.ru