

По вопросам продаж и поддержки обращайтесь:

Архангельск (8182)63-90-72	Калининград (4012)72-03-81	Нижний Новгород (831)429-08-12	Смоленск (4812)29-41-54
Астана +7(7172)727-132	Калуга (4842)92-23-67	Новокузнецк (3843)20-46-81	Сочи (862)225-72-31
Белгород (4722)40-23-64	Кемерово (3842)65-04-62	Новосибирск (383)227-86-73	Ставрополь (8652)20-65-13
Брянск (4832)59-03-52	Киров (8332)68-02-04	Орел (4862)44-53-42	Тверь (4822)63-31-35
Владивосток (423)249-28-31	Краснодар (861)203-40-90	Оренбург (3532)37-68-04	Томск (3822)98-41-53
Волгоград (844)278-03-48	Красноярск (391)204-63-61	Пенза (8412)22-31-16	Тула (4872)74-02-29
Вологда (8172)26-41-59	Курск (4712)77-13-04	Пермь (342)205-81-47	Тюмень (3452)66-21-18
Воронеж (473)204-51-73	Липецк (4742)52-20-81	Ростов-на-Дону (863)308-18-15	Ульяновск (8422)24-23-59
Екатеринбург (343)384-55-89	Магнитогорск (3519)55-03-13	Рязань (4912)46-61-64	Уфа (347)229-48-12
Иваново (4932)77-34-06	Москва (495)268-04-70	Самара (846)206-03-16	Челябинск (351)202-03-61
Ижевск (3412)26-03-58	Мурманск (8152)59-64-93	Санкт-Петербург (812)309-46-40	Череповец (8202)49-02-64
Казань (843)206-01-48	Набережные Челны (8552)20-53-41	Саратов (845)249-38-78	Ярославль (4852)69-52-93

сайт: www.zoomlion.nt-rt.ru || эл. почта: znm@nt-rt.ru

TECHNICAL DATA

Item (unit: mm)	ZE1250E	ZE1250Esp	
Total length	16000	14700	
Total width	5652	5652	
Total height(to the top of boom)	6400	6400	
Slewing radius of tail	4980	4980	
Tail length	4800	4800	
Ground clearance of counterweight	1848	1848	
Min. Ground clearance	990	990	
Ground contact length of track	5200	5200	
Track length	6615	6615	
Track gage	3900	3900	
Track shoe width	700	700	
Track height(to the top of cab)	4289	4289	
Rotary table width	5492	5492	
Item	Unit	ZE1250E	ZE1250Esp
Working mass	Kg	119000	120000
Standard bucket capacity(SAE)	M³	5.3	7
Rated power	kW	567	
Engine model	--	Cummins QSK23	
Max. torque	N.m/rpm	3448/1350	
Traveling speed (high/low)	Km/h	3.22/2.17	
Slewing speed	rpm	5.5	
Gradeability	--	35° (70%)	
Max. drawbar pull	kN	735	
Max. Digging force of arm (ISO)	kN	450	445
Max. Digging force of bucket (ISO)	kN	545	578

WORKING RANGE

Item (unit: mm)	ZE1250E	ZE1250Esp
Max. excavating distance	15355	14110
Max. horizontal excavating distance	14985	13710
Max. excavating depth	13150	12950
Max. vertical excavating depth	8650	8380
Max. excavating height	9425	8000
Max. dumping height	6900	4840
Min. slewing radius	7960	6470

EXCAVATOR



ZE1250E

